

Before Starting Work.

SITITAMRAD CEMENT MIXES AND CONTACT

- Wet cement mix is a substance that can
- where the substance was in contact with the when the skin reacts to certain substances. The resh can vary but it is usually ritchy and causes flaky skin. The resh occurs only 2. Contact dermatitis is a rash that may occur cause contact dermatitis.
- Nont eyes and seek medical advice it you get your skin immediately. Thoroughly rinse out Wash cement or plastic or plaster mixes off .uixs
- er contact. If the rash persists se Wild dermattis will heat providing there is no any type of cement mix in them.

medical advice.

BEFORE STARTING WORK

- 1. Do not use this cement mixer where there is **WORK AREA**
- from breathing toxic fumes, do not run mi To reduce the risk of serious or fatal injury .s from petrol, or gas cylinders. seuuni enuli וו אווו ומעוני אוו seuuni enuli
- when working in other contined areas. Ensure that you have proper ventilation nous uniess you have good venuation.
- and that no-one is near to you of could 3. Make sure that the area is clear and sate
- distract you.
- around your work area, put partiers around dust, warn others to keep away, put barriers Protect other people from the noise and

your work area.

mixer. Particular jobs or environments may equipment (ppe) are the minimum that

SROTAR390

3YT TEB Iludilos

The Crescent Birmingham Business Park

vesociation ⊨urope

มกอา ระบอดอา กระ

2701 Safety Guidance

It is important to read this entire leaflet

BEFORE using the Belle Minimix Cement Mixer

Plan your work and think ahead to make sure you will always

Electricity can be hazardous and must always be used with

Electricity and water make a very dangerous combination.

Cement mixes are harmful to eyes, lungs and skin. Follow any

instructions given by the manufacturers of these cement products.

compounds with water. It can also mix composts and other similar materials.

EN345 or BS1870/4972; gloves; rcd if using a 230 volt (mains) supply.

effort has been made by HAE/EHA to ensure that the information given in this docum

:lism3

3.

·G

•

3

·7

company.

:euoudeie

Dine industrial plug.

Keep electrical equipment away from rain and water.

machine works before you start on the main task.

vuse.org.u

44 (0) 121 333 4109

either a normal square pin plug fitted, or a

to run directly from 230v mains will have

been supplied, take care not to injure yourself when moving it about - it may be heavier than you think. Machines designed

230v supply. If a portable transformer has

to power the machine from a normal mains

110v supply. The hire company will have provided a portable transformer if you need

plug fitted are designed to run off a special

Machines with a cylindrical yellow industrial

do not use the mixer - contact the hire

and stand. If anything is found damaged,

also need to wear appropriate personal

full trousers to prevent the mixes coming

You should wear gloves, long sleeves and

You must wear safety boots (EN345 or

EFP3(s) protection) when you are mixing

You will need to wear an appropriate

You must wear goggles (EN166 or BS2092)

vhen you are working with this machine.

6. Anybody who is working near to you will

1. Check your machine, cables, plugs, drum

BELLE MINIMIX CEMENT MIXER

into contact with your bare skin.

materials that cause dust.

hiorecrive equipment.

·(Z/6t/0/8LSB

Check that the plug on your machine matches your supply. Do not try to force

connections or improvise them.

Belle Minimix Cement Mixer

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

This Belle minimix cement mixer is designed for mixing concrete, mortar, plaster and similar

The action of this mixer can cause injury or damage if the machine is not used in a careful

If you have not used a Belle mini mix cement mixer before, familiarise yourself with how the

You must have at least the following items of personal protective equipment: goggles:

EN166 or BS2092; dust mask - a minimum of EN149 FFP3(s) protection; safety boots to

This machine must not be used by minors, or by anyone under the influence of drugs or

This Belle mini mix cement mixer is designed for operation by an able bodied adult. Anyone

with either temporary or permanent disability must seek expert advice before using it.

is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments

have the force of law and only the courts can authoritatively interpret the law.

For guidance on managing

construction health risks go to

www.hse.gov.uk/construction

n HAE by Banner Plant Limited, Li **Using the Belle Minimix Cement Mixer**

4

5.

2

3

4.

6

7.

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

.s

JO

OWI

110 VOLT MACHINES (YELLOW PLUG)

given any special instructions, you should

only use a suitably rated heavy duty 110v

extension cable, not longer than 50 metres

(160 feet). You must only use an extension cable between the transformer and the

Lay the extension cable out carefully

avoiding liquids, sharp edges, doorways

or windows where it might be trapped, and

places where vehicles might run over it.

Unroll it fully or it will overheat and could

Make sure that any extension cable

socket. Plug your machine into the rcd. This will help to protect you against electric

shock if the cable or machine get

Use the "TEST" button to check that the

rcd is working each time you use it. Reset the rcd according to the instructions

ELD

皀

2450 Regents Court

lihull B37 7YE

The C

T

connections are dry and safe.

230 VOLT MACHINES (SOUARE PIN OR BLUE PLUG)

Use a residual current

device ("rcd") plugged

directly in to the 230 volt

If you need an extension

cable, follow any special

hire company. If the hire company have not given

any special instructions.

you should only use a

instructions given by

ntinued)

machine

catch fire.

damaged

supplied with it.

(...iseaned overleat...)

100

company. If the hire company have not

any special instructions given by the hire

əuı h

It you need to use an extension cable, follow

any 230v extension cable

1. If you are using a portable

tor your machine.

YTERCAL SAFETY

ocking clip.

.s

UNAIS

saretully.

ransiormer,

230 volt socket. Do not use

transtormer directly into the

6nid

110 VOLT MACHINES (YELLOW PLUG)

voltage: it will be 100v or 230v.

ue dionua is undrea, use two people:

J. Your machine will lonely operate on one

normal square pin plug titted, or a blue industrial plug. Read the instructions below

machines will have a yellow industrial plug

If you feel the mixer/stand is too heavy or if

clip. Tilt the stand and mixer back into the upright position. Make sure it is firmly sited.

-ocate the stand into position and lock the

that it stands on the opening of the drum.

Alternatively one man can tip the mixer so

mixer onto the stand and secure with the

The stand should be sited on firm level

which raises the height of the mixer to make it easy to empty the drum into a wheelbarrow. The mixer can be used with

Reverse this procedure to refit the drum,

When it has fully unscrewed, lift the drum off

J. Your Belle minimix is supplied with a stand,

take care not to damage the threa

3. Two persons can then lift and locate the

ground near to your work area.

or without the stand.

3

1.

3

1.

2.

3

6

10

pauh

be working safely.

and controlled way.

alcohol

great care.

suitably rated heavy duty one, not longer than 50 metres (160 feet). Plug it directly

Lay it out carefully avoiding liquids, sharp

edges, doorways or windows where it might be trapped, and places where vehicles might run over it. Unroll it fully or

Make sure that any extension cable connections are dry and safe.

Wear your protective equipment including

Do not move the mixer while the drum is full.

Do not move the mixer while it is still connected to the power supply.

damaged in any way, switch off and

unplug at the mains before inspecting it. If

the cable attached to the mixer is damaged, stop using the machine.

extension cable has been damaged, do

Take care not to accidentally pull the plug

Switch off and remove the plug from the

socket before leaving the mixer

If your equipment does not work properly

Please keep this leaflet safely as it may be

do not attempt to repair it. Contact the hire

required for future reference

121 380 4600

e.org.uk www.hae.org.uk

44 (0) 121 333 4109

the mixer and turn the drum anticlockwise.

transportation, switch off, stand in front of

rotating drum will greatly assist removing

shovels full of clean gravel, with water, in the

To remove the drum for storage

b. Always store the mixer in its normal upright

any stubborn residue of the mix.

perore the cement mix hardens.

the drum and the mixer is washed cl

2. When you have finished work, make sure

Ensure the drum is rotating while emptying

wer is switched off. Keep your hands out

powertul. It will not stop rotating until the

other than the mix into the drum while it is

full load would be difficult and would strain

loading. Do not load a concrete mix into a stationary drum. Starting the mixer with a

mixer is switched off before you plug it into

before you switch the mixer on, you must know how to stop it. Make sure that your

Check on how the on/off switch operated -

4. Check that the mixer is sited firmly and

safely near to your work area.

1. Always start the drum rotating before

2. Do not put your hand, shovel or anything

3. The rotation of the drum is slow but very

be cut or

If any

-2

.nonisoq

.XIIII ƏLI

or the way.

.6013103

мона

·9

.Viddus em

The drum shart.

it will overheat and could catch fire

USING THE BELL MINIMIX

ear defenders and goggles

If you think the cable may

Contact the hire company.

not use it again.

from the socket.

nattended.

company.

into the rcd.

CEMENT MIXER

1. The following items of personal protective

Banner

v⁰³²⁰¹⁷

require a higher level of protection.