

AAHA XHOW

- fumes from petrol or gas cylinders. there is a danger of explosion. It may ignite Do not use electrical equipment where 1
- Keep electrical equipment away from rain
- distraction. Warn others to keep away; that no-one can come close to cause Ensure the work area is clear and safe and 3 and water.
- neater, and can cause paper and cloth to as much heat as a 1kw electric radiant near to the lights. Some lights can produce Ensure there are no combustible materials necessary. partiers or warning signs may be
- be be safe from vehicles, people, war Set up the lights in an area where they will rubbish can be blown close to the light. Check that no loose paper or .91ingi
- over. The ground should be firm and level. which may damage them or knock them rain, strong gusts of wind and other hazards
- not form a tripping hazard in doorways or ı, and so that the cables themselves d Lay out the cables to avoid damaging .9

- THƏIJ S'ABABTSAJA waikways.

Banner

- Check the equipment including cables 1 ΤΗΘΙ ΞΙΒΑΤΑΟΡΟΝΑΑΤ
- found damaged, do not use it contact the upports the light properly. If anything is plugs and sockets; check that the stand
- the supply. Do not try to force connections Check that the plugs on the cables match .s uite company.
- bing titted are designed to run off a special Lights with a cylindrical yellow industrial 31 or improvise them.
- brovided a portable transformer if the lights 110v supply. The hire company will have

3YT TEB Iludilos The Crescent Birmingham Business Park vesociation ⊨urope

noo sinegen uce

:lism3 :euoudeie

3

.2

-1

3.

.s

٠.

·t

a chain of lights.

STHRILINK LIGHTS

·*k*iddns

1025 Safety Guidance

It is important to read all of this leaflet

BEFORE you use the Plasterer's Light

may occur so they can be dealt with safely.

1.

2.

3.

5.

6.

7

rain

with great care.

drugs or alcohol.

Plan each task and try to foresee any problems that

Electricity is hazardous and must always be used

Water and electricity make a very hazardous

they are easily adjustable and quickly transportable.

RCD if using a 230 volt (mains) supply

The following items of personal protective equipment are a minimum:

temporary or permanent disability must seek expert advice before using it.

Plasterer's Light

and similar lights

Tasklight – Contractor's Light

Failsafe Light – Upright Light

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment. This leaflet is not a substitute for a properly executed risk assessment.

combination. Do not splash water on the electrical parts and keep the equipment out of the

These lights are designed to provide almost shadow free illumination on walls and ceilings;

These lights must not be installed or used by minors, or by anyone under the influence of

These lights are designed for installation and use by an able bodied adult. Anyone with either

Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting materia

from the use of any such document/material. Only Acts of Parliament and Statu have the force of law and only the courts can authoritatively interpret the law.

is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perc nave arisen from the use of any such document/material. Only Acts of Parliament and Statutory Ins

this is permissible.





unless you have specific instruction that

Do not plug a power tool into the light chain

stated. If unsure - ask the hire company.

adding more units than the maximum

Do not overload the electrical system by

single units, or to be linked together to form

se pash ag of man briwolls staypos/solid

nipment regarding batteries and charging.

the hire company or labels attached to the

addition follow any verbal instructions from

The guidance in this leaflet still applies; in

automatically provide up to 3 hours f safety

normally runs on mains supply but will

The light may be a fail-safe light that

used in a place where there is no mains

cuarged from a mains supply before it is

The light may be a portable light that is

230V mains will have either a normal square

Equipment designed to run directly from

t to injure yourself when moving it about

If a portable

rransiormer nas been supplied, take care

are required to be powered from a normal

ЧИНА И ВАТТЕВҮ ВАСКИР

- it may be heavier than you think.

mains 230v supply.

pin plug fitted, or a blue industrial plug.

light should the mains supply tail.

Some of these light units are fitted with



to have arisen t



44 (0) 121 380 4600

e.org.uk

44 (0) 121 333 4109

.pagemag

Eh.

- secure any screws or clips.
- replace all covers and guards properly, and 6. When the tube or bulb has been changed,
- life; use clean cloth or tissue paper. with bare tingers - this will shorten the bulb's
- 5. Do not touch replacement halogen bulbs ixing screws or clips.
- 4. Open any covers taking care not to lose any 'IIIeIII
- lights to cool down before safely handling 3. It may be necessary to wait for high power
- off and unplug the faulty light.
- when switching off several lights. Then switch Z. Ensure that no-one will be put in danger it
- Check with the hire company if in any doubt. inorescent tupe or halogen buib ready. 1. Make sure you have the correct replacement

TUBES OR HALOGEN BULBS CHANGING FLUORESCENT

are dry and sale.

- xtension cable connec suλ 5. Make sure that
- and could catch fire.
- Unroll it tully or it will overheat vehicles might run over it.
- ball trapped, and places where εσθεε' σοοιωςλε οι ωισσως ωμείε τι μιθμι ρε
- 4. Lay it out carefully avoiding liquids, sharp Plug it directly into the rca.
- duty one, no longer than 50 metres (160 feet). hire company have not given any special instructions, only use a suitably rated heavy
- instructions given by the hire company. If the required, follow any special 3. If an extension cable is

ti utiw pailqqus according to the instructions

驷

Before Starting Work...









below tor each type.



(SQUARE PIN OR BLUE PLUG)

cable connections are dry and

will overheat and could catch

vehicles might run over it. Unroll it fully or it

where it might be trapped, and places where

liquids, sharp edges, doorwarys or windo

3. Lay the extension cable out carefully avoiding

extension cable between the transformer a

rated heavy duty 110v extension cable, no longer than 50 metres (160 feet). Only use an

any special instructions only use a suitably

company. It the hire company have not given

special instructions given by the hire

2. If an extension cable is required, follow any

transformer directly into the 230 volt socket

1. If using a portable transformer, plug the

It will be 110v or 230v. Head the instructions

The equipment will only operate on one voltage:

Do not use any 230v extension cables

110 ЛОГІ ГІСНЦІЙС (ЛЕГГОМ БГЛС)

4. Ensure sure that any extension

530 AOEL FIGHLING

.ent

ີບານອີ້ມີ ອີ້ນ

1

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

For guidance on managing

construction health risks go to

www.hse.gov.uk/construction

Using the Plasterer's Light

Ensure that nobody is looking into the light before switching it on - the brightness

If a cable appears to be cut or damaged in any way, switch off and unplug the

If the cable attached to a light is damaged, stop using the light. Contact the hire company. If an extension cable has been damaged, do not use it again.

Ensure that no combustible material, such as paper or rubbish, is too close to

Switch off lights and unplug before moving them or adjusting their position. With

Switch off and unplug before leaving the transportable lights unattended.

10. Before switching off any lighting, ensure no one is going to be put in danger by

11. If the lights are left in place for more than a week, then a competent person should

12. If your equipment does not work properly, do not attempt to repair it. Contact the

Please keep this leaflet safely as it may be required for reference at a future date

(transportable light)

Do not hang or drape cables, strings or anything else over the lights.

Check that cables are laid out safely and are not causing a hazard.

Take care not to trap fingers when erecting the stands

halogen lights allow to cool a short while before moving.

inspect them every week to make sure that they are safe.

Hire Association Europe

m Business Park

2450 Regents Court

olibull B37 7YE

The Crescent

can cause temporary blindness.

supply before inspecting it.

powerful and hot lights.

the drop in lighting levels.

hire company.

1.

2.

3. 4.

5.

6.

7.

8.

9.

- and switched on powerful lights can dazzle. 7. Do not look into the light as it is plugged in