



Using the Compressor

TOWING

1. Check the compressor drawbar and towing hitch carefully for damage and security.
2. Check the tyres; never tow or move the compressor with a flat tyre as it will be unstable.
3. Make sure that the towing vehicle is capable of safely towing the weight of the compressor, and that it towing hitch is in good condition, and comparable with the one fitted to the compressor.
4. If the coupling is of the pin and eye type, the pin must have a suitable R-clip or over-centre clip to prevent it jumping out.
5. Fit any security chain, making sure that there is adequate length free to allow cornering and towing over rough ground. The end of the security chain fixed to the two vehicles must be attached to a sufficiently strong point.
6. Connect any electric cable for warning lights and signals – and check that they work at the rear of the compressor. If you are going onto the public road, make sure that the towing vehicle's registration number is properly displayed at the rear of the compressor.
7. Make sure that any jockey wheel or jack leg is fully raised and fixed so that it will not drop during transport.

USING THE COMPRESSOR

1. Wear your protective equipment including ear defenders and goggles.
2. Use only tools and equipment supplied by the hire company with this compressor.
3. Check that any air lubrication container is topped with the recommended oil.
4. Check that the hose couplings are clean before you connect hoses together. Blow out

the hoses before you connect a tool to remove condensation.

5. When you have set up the compressor, start up and check that everything operates properly.
6. Ensure there are no apparent air leaks.
7. You should run the compressor with the covers closed to reduce noise levels. If you need to run it with the covers open they should be properly supported with a secure locked stay so they cannot vibrate loose and slam shut causing injury or damage.
8. At intervals, while working, stop and check for air leaks or other possible faults. Check the oil level in the container at the same time.
9. Watch out for signs that vibration from the work may be affecting your hands. If your fingers start to tingle or feel numb, take a short break from work. Exercise your fingers to encourage blood circulation.
10. To help prevent vibration affecting your hands, operate the machine for shorter periods. Keep hands warm – wearing gloves may help do this.
11. Stop work if someone approaches you.
12. You must stop the compressor and release the air pressure before you disconnect any part of your equipment.
13. Stop the engine and release the air pressure before you leave the compressor unattended.
14. If your compressor does not work properly, do not attempt to repair it. Contact the hire company.

Please keep this leaflet safely as it may be required for future reference



Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Solithull B37 7YE

Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

1. This section describes the starting procedure for most diesel engines.
2. If the hire company has given special instructions, follow them. Otherwise follow the instructions given below.
3. Check the oil and fuel levels before attempting to start the engine.
4. Move the STOP control to the RUN position.
5. Check the throttle lever is in the IDLE position.
6. Do not wear gloves when starting the engine.
7. Also, ensure there is no loose clothing or flapping sleeves that could get caught.
8. Fit the starting handle to the shaft, and check that the starting handle is in the correct position.
9. Move the decompression valve lever into the decompression position.
10. If the engine is fitted with a cold start button, press it in when starting from cold.
11. Grasp the starting handle firmly in one hand but do not wrap your thumb around the handle. Keep it on the same side as fingers – this is very important. Your thumb could be broken if it wrapped around the handle and the engine kicks back.
12. Crank the engine strongly before lowering the decompression lever smoothly. The engine should fire up – if it doesn't go through the steps again from instruction 7 above.
13. If the engine is now running, slide the handle off the shaft.
14. If you let go of the handle when the engine fires up, do not try to grab it. Stop the engine using the STOP control. Then start the engine again.
15. In cold weather, allow the engine to warm up before commencing work.
16. Never stop the engine using the decompression lever. This may damage the engine and will be regarded as misuse by the hire company. Only use the proper RUN/STOP control.

STARTING THE ENGINE

9. Replace all fuel caps properly and leave the fuel container in a safe, cool place.



Before Starting Work...

Towable Road Compressor


The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

It is important to read this entire leaflet BEFORE using the Towable Road Compressor

1. Plan the use of the Towable Road Compressor so that it can always be used safely.
2. Diesel fuel is highly flammable. Take care not to cause a fire or explosion.
3. Compressed air can be hazardous and must be used carefully. Never aim a jet of compressed air at anyone.
4. This road compressor is designed to produce compressed air at its rated pressure to enable you to run one or more compressed air tools simultaneously.
5. The action of this road compressor can cause injury or damage if the equipment is not used, and moved, in a careful and controlled way.
6. You should not use this compressor unless you have had previous experience, or you have had a course of instruction from a responsible body.
7. You should have at least the following items of personal protective equipment: impact resistant goggles: EN166 – B or BS2092 grade 1; ear muffs or plugs giving protection for levels up to 102dB(A); safety helmet to EN397 or BS5240; safety boots to EN345 or BS1870/4972; high visibility vest or clothing; gloves.
8. This compressor must not be used by minors, or by anyone under the influence of drugs or alcohol.
9. This compressor is designed for operation by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it.

WORK AREA

1. Do not use this road compressor where there is a danger of explosion. It will ignite fumes from petrol or gas cylinders.
2. Using this equipment indoors or in confined spaces could cause fatal carbon monoxide poisoning. Never use it in domestic premises and only use it in other indoor situations if its suitability and the ventilation required has been fully assessed. Mechanical extraction ventilation will almost always be required.
3. Make sure that your work area is clear and safe and that no-one is near to you or could distract you.



Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting material is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.

(continued overleaf)

©Copyright Hire Association Europe April 2011

1. Check your equipment, hoses, gauges, and tools. If anything is found damaged, do not use the compressor – contact the hire company.
2. Check the oil and fuel levels and top up if needed. Check that all the outlet valves are shut.
3. Use only the air hoses supplied by the hire company.
4. Usually, compressed air carries a minute amount of oil-mist to prevent any air tools seizing up. Make sure the lubrication container on your compressor is topped up with the recommended oil. Check the level regularly.
5. Do not obstruct or prevent safety devices from working.
6. Do not try to run the compressor at a greater pressure than recommended.
7. Do not connect or disconnect any tool or pipe while the system is pressurised, release the pressure first.
8. Do not use tools with a worn shank or cutting edge, they are more likely to break or cause vibration from using some air-powered tools can be hazardous. Warm your hands up before you start work, and wear gloves to keep your hands warm while you are working.
9. Check the controls and find out how your compressor operates – before you start it up, you must know how to stop it.
10. Compressed air can cause serious injuries if it is misused. You must not use it in an unauthorised way or without correct equipment.
11. Set the handbrake and secure the jacking leg. Check the wheels with suitable wedges or timber off-ends. Do not rely on just the handbrake especially if you have sited the compressor on a sloping surface.
12. The following items of personal protective equipment (PPE) are the minimum that should be worn whenever you use this road compressor. Particular jobs or environments may require a higher level of protection.
13. You must wear impact resistant goggles (EN166 – B or BS2092 grade 1) when you are working with this compressor.
14. This compressor is likely to cause noise levels up to 102 dB(A) – wear appropriate ear muffs or plugs giving hearing protection for this level as a minimum.
15. You must wear safety boots (EN345 or BS1870/4972).
16. You must wear a safety helmet (EN 397 or BS5240) when using this machine on a construction site.
17. You should wear a reflective vest or similar high visibility garment on a construction site or when working near roads.
18. Gloves may help keep your hands warm to reduce the effect of vibration, and also to protect from minor injuries.
19. Anybody who is working near to you will also need to wear appropriate personal protective equipment.
20. Set the handbrake and secure the jacking leg. Check the wheels with suitable wedges or timber off-ends. Do not rely on just the handbrake especially if you have sited the compressor on a sloping surface.

WORK AREA (continued)