



Redistributed under licence from HAE by Banner Plant Limited. Licence expires on 31/05/2025

Using the Pump

1. Wear the protective equipment if working on or near the pump.
2. Set the pump in position and connect the suction hose and strainer, ensuring the strainer is not blocked and is completely submerged. If there is an air leak in the suction hose, the pump will not work efficiently. Do not use this pump without the strainer properly attached.
3. Connect the discharge hose and lay it out carefully to the selected discharge area.
4. After starting the engine, the pump will start pumping the water immediately.
5. If the pump operates but fails to pump water effectively, it is probably because there is an air leak in the suction hose or connection, or the strainer is not fully immersed; or the strainer is blocked.
6. When pumping dirty waters with solids in suspension, the strainer may need regular cleaning.
7. Stop the engine before re-siting the unit; moving hoses; or cleaning the strainer or any filters.
8. Keep a check on the discharge area to make sure that no hazard is being created. Do not pollute rivers or drains – if in doubt check with the hire company or local Environment Agency – their number will be in the telephone directory.
9. Do not allow vehicles to run over the hoses at any time, unless a layflat discharge hose is being used.
10. After pumping dirty or contaminated water flush the pump through with clean water if possible.
11. In cold weather prevent the pump from freezing up when not in use – contact the hire company if a lot of work is planned in freezing conditions.
12. To protect the engine and help starting it is advisable to keep the machine under cover when not in use.
13. If the equipment does not work properly do not attempt to repair it. Contact the hire company.
14. Please store this leaflet safely. It may be required for further information.

Please keep this leaflet safely as it may be required for future reference



Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Soliuhll B37 7YE

Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

It is important to read this entire leaflet BEFORE using the Pump

1. Diesel fuel is flammable – take care not to cause a fire or explosion.
2. This pump is designed for pumping clean and dirty water with solids in suspension, on building sites and other similar places.
3. Pumping water can cause damage and possibly injury if the operation is not planned and controlled.
4. If the operator has not used this type of water pump before, they should familiarise themselves with the equipment before starting work.
5. The work should be thought out and planned ahead to ensure that it will always be carried out safely.
6. The following items of personal protective equipment must be worn as a minimum:
Ear muffs or plugs giving protection for levels up to 95 dB(A);
Dust mask – a minimum of EN149 FFP3(s) protection;
Gloves.
7. This equipment must not be used by minors, or by anyone under the influence of drugs or alcohol.
8. This pump is designed for operation by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it.



Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting material is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk

Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Soliuhll B37 7YE

1. If the hire company has given special instructions follow them. Otherwise, instructions follow this leaflet.
 2. Check the oil and fuel levels before trying to start the engine.
- ### STARTING AND STOPPING THE ENGINE
1. If any fuel is spilled on clothes, they should be changed straight away.
 2. Put all fuel caps back on properly, and move the fuel can to a safe, cool place.
 3. Crank the engine strongly before lowering the decompression lever smoothly. The engine should fire up.
 4. If the handle is now running, slide the handle off the shaft.
 5. If the engine is now running, slide the handle off the shaft.
 6. If the engine is now running, slide the handle off the shaft.
 7. If the engine is now running, slide the handle off the shaft.
 8. If the engine is now running, slide the handle off the shaft.
 9. If the engine is now running, slide the handle off the shaft.
 10. Crank the engine strongly before lowering the decompression lever smoothly. The engine should fire up.
 11. If the engine is now running, slide the handle off the shaft.
 12. If the handle is now running, slide the handle off the shaft.
 13. To stop the engine use the RUN / STOP control. Never stop the engine using the decompression lever. This may damage the engine and will be regarded as misuse by the hire company.
- ### REFUELLING
1. No smoking.
 2. Stop the engine and let it cool down.
 3. Clean the filler cap and the area around it to prevent dirt falling into the fuel tank.
 4. Use a funnel when refuelling. Do not spill any fuel on persons or the machine.
 5. Wipe any fuel off the machine.
 6. Dispose of fuel soaked cloth carefully.
 7. If any fuel is spilled on the ground, wipe it up or cover it with soil.
 8. If any fuel is spilled on clothes, they should be changed straight away.
 9. Put all fuel caps back on properly, and move the fuel can to a safe, cool place.
- ### OPERATORS
1. The following items of personal protective equipment (ppe) are the minimum that should be worn whenever this pump is used. Particular jobs or environments may require a higher level of protection. This equipment is likely to cause noise levels up to 95 dB(A) – appropriate ear muffs or plugs must be worn giving protection for this level as a minimum.
 2. Dirty or stagnant water can contain harmful bacteria and other hazards. Cover any cuts or broken skin with waterproof dressings. Wash hands before smoking, eating or drinking.
 3. Wearing waterproof gloves can help to protect the hands.
 4. Anyone who is working nearby will also need to wear personal protective equipment.
 5. Check the area where the water will be discharged. Make sure that a hazard will not be created for persons or the environment.
 6. Contaminated water and other liquids that are hazardous to the environment must not be discharged into rivers or down drains.
 7. There will be a limit on how high the equipment can pump water – this is sometimes called the 'head'. If a strainer fitted to the inlet hose. Do not operate this pump without the strainer fitted to the inlet hose.
- ### Before Starting Work...
1. Do not use this pump where there is a danger of explosion. It will ignite fumes from petrol, or gas cylinders.
 2. Using this equipment indoors or in confined spaces could cause fatal carbon monoxide poisoning. Never use it in domestic premises and only use it in domestic situations if its suitability has been fully assessed. Mechanical extraction ventilation will almost always be required.
 3. If there is a risk of falling into the water to be pumped, make sure that the area is clear and safe and that no distraction.
 4. If the work involves pumping contaminated water or other liquids that may be hazardous to the environment, check first with the hire company or local Environment Agency – their number can be found in the telephone directory.
 5. Ensure the pump is sited on a firm level base; secure it to prevent accidental movement.
 6. Route the suction and discharge hoses where they will not be damaged by vehicles. Also make sure that they will not create a hazard to vehicles or people.
 7. Check the area where the water will be discharged. Make sure that a hazard will not be created for persons or the environment.
 8. Contaminated water and other liquids that are hazardous to the environment must not be discharged into rivers or down drains.
 9. There will be a limit on how high the equipment can pump water – this is sometimes called the 'head'. If a strainer fitted to the inlet hose. Do not operate this pump without the strainer fitted to the inlet hose.

v:032017

©Copyright Hire Association Europe April 2011



WORK AREA